

***Town of Stockton Springs
217 Main St.
P. O. Box 339
Stockton Springs, ME 04981
Tel: 207-567-3404 Fax: 207-567-3710***

Request for Bids
Cab & Chassis

The Town of Stockton Springs invites sealed bids for a cab and chassis. Bids must be for the latest model (2018 or 2019) cab and chassis in accordance with the requested specifications. Trade In: 2008 (7400 Series) International dump-body truck, with plow, wing, and sander. This truck can be viewed at the Public Works garage 194 Cape Jellison Road, Stockton Springs or upon request, contact Public Works Foreman George Russell at (207) 567-3408.

Items to be included with bid: Bid Form
Warranty information
Full Specification sheet

Successful bidder is required to supply upon delivery, one (1) copy of operating manual or equivalent for equipment quoted.

Bids must be received by the Stockton Springs Town Office by **2:00 PM, Monday, July 16th, 2018**, at which time they will be publicly opened and read aloud. Submitted bids must be in a sealed envelope, plainly marked "Cab & Chassis Bid," and addressed to the Purchasing Agent, Town of Stockton Springs, P.O. Box 339, Stockton Springs, ME 04981 or emailed to manager@stocktonsprings.org with "Cab & Chassis Bid" in the subject line.

Contact Town Manager Courtney O'Donnell at (207) 567-3404 with any questions concerning the bid process. Contact Public Works Foreman George Russell with any questions related to the vehicles or trade in at (207)567-3408.

The Town of Stockton Springs is a tax-exempt municipality. The Town reserves the right to accept or reject any or all bids and to negotiate with the bidder who submits the most advantageous bid as deemed by the Town.

Town of Stockton Springs
217 Main St.
P. O. Box 339
Stockton Springs, ME 04981
Tel: 207-567-3404 Fax: 207-567-3710

BID FORM

Please print clearly

Truck Price: \$ _____

Less: Trade In Value: \$ _____

Total Amount of Bid: \$ _____

Make, Model, Year: _____

Expected Delivery Date: _____

Business Name:	
Street or PO Box:	
City, State, Zip:	
Telephone Number:	
Email Address:	
Contact Name:	
Title:	
Date:	

Bid Specifications

Model Profile

2018 7400 SFA 4X2 (SA626)

APPLICATION:	Front Plow and Wing with Spreader
MISSION:	Requested GVWR: 43000. Calc. GVWR: 41180 Calc. Start / Grade Ability: 35.88% / 2.49% @ 55 MPH Calc. Geared Speed: 75.9 MPH
DIMENSION:	Wheelbase: 183.00, CA: 108.00, Axle to Frame: 63.00
ENGINE, DIESEL:	{Cummins L9 330} EPA 2017, 330HP @ 2000 RPM, 1000 lb-ft Torque @ 1400 RPM, 2200 RPM Governed Speed, 330 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 3500 RDS} 5th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, SINGLE:	{Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, Driver Controlled Locking Differential, 200 Wheel Ends Gear Ratio: 5.38
CAB:	Conventional
TIRE, FRONT:	(2) 315/80R22.5 Load Range LX WORKS Z (MICHELIN), 485 rev/mile, 65 MPH, All-Position
TIRE, REAR:	(4) 11R22.5 Load Range H XDN2 (MICHELIN), 497 rev/mile, 75 MPH, Drive
SUSPENSION, RR, SPRING, SINGLE:	Vari-Rate; 31,000-lb Capacity, Includes 4500-lb Capacity Multileaf Auxiliary
PAINT:	Cab schematic 100GM Location 1: 2303, Red (Std) Chassis schematic N/A

Vehicle Specifications
2019 7400 SFA 4X2 (SA625)

Description

Base Chassis, Model 7400 SFA 4X2 with 183.00 Wheelbase, 108.00 CA, and 63.00 Axle to Frame.

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.433" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL

BUMPER, FRONT Steel, Swept Back; Painted 0001 Canyon Black

WHEELBASE RANGE 146" (370cm) Through and Including 195" (495cm)

AXLE, FRONT NON-DRIVING (Meritor MFS-20-133A) Wide Track, I-Beam Type, 20,000-lb Capacity

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

SHOCK ABSORBERS, FRONT

SUSPENSION, FRONT, SPRING Multileaf, Shackle Type, Single Stage Spring; 20,000-lb Capacity; Less Shock Absorbers

Includes

: SPRING PINS Rubber Bushings, Maintenance-Free

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

SPRINGS, FRONT AUXILIARY Air Bag, Right Side Only, Driver Control

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon
 : DRAIN VALVE Twist-Type
 : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster
 : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel
 : PARKING BRAKE VALVE For Truck
 : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4
 : SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes)
 : SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes)
 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

Notes

: Rear Axle is Limited to 23,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered

BRAKES, FRONT, AIR CAM 16.5" x 6", Includes 24 SqIn Long Stroke Brake Chambers

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck

DRAIN VALVE (Berg) with Pull Chain, for Air Tank

Includes

: DRAIN VALVE Mounted in Wet Tank

AIR BRAKE ABS (Bendix AntiLock Brake System) Full Vehicle Wheel Control System (4-Channel)

AIR DRYER (Bendix AD-9) with Heater

Includes

: AIR DRYER LOCATION Inside Left Rail, Back of Cab

BRAKE CHAMBERS, REAR AXLE (Bendix EverSure) 30/30 Spring Brake

Vehicle Specifications
2019 7400 SFA 4X2 (SA625)

Description

BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn

BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake

Notes

: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.

AIR COMPRESSOR {Cummins} 18.7 CFM Capacity

AIR TANK Painted Aluminum, with Straight Thread O-Ring Ports

STEERING COLUMN Tilt

STEERING WHEEL 2-Spoke, 18" Dia., Black

STEERING GEAR (2) {Sheppard M100/M80} Dual Power

AFTERTREATMENT COVER Steel, Black

EXHAUST SYSTEM Single Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab; for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab

■ **ENGINE EXHAUST BRAKE** for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

TAIL PIPE (1) Turnback Type, Non-Bright, for Single Exhaust

EXHAUST HEIGHT 10'

MUFFLER/TAIL PIPE GUARD (1) Non-Bright Aluminum

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: **DATA LINK CONNECTOR** For Vehicle Programming and Diagnostics In Cab

: **HAZARD SWITCH** Push On/Push Off, Located on Top of Steering Column Cover

: **HEADLIGHT DIMMER SWITCH** Integral with Turn Signal Lever

: **HEADLIGHTS (2)** Halogen, Round, with Chrome Plated Bezels

: **JUMP START STUD** Located on Positive Terminal of Outermost Battery

: **PARKING LIGHT** Integral with Front Turn Signal and Rear Tail Light

: **STARTER SWITCH** Electric, Key Operated

: **STOP, TURN, TAIL & B/U LIGHTS** Dual, Rear, Combination with Reflector

: **TURN SIGNAL SWITCH** Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature

: **WINDSHIELD WIPER SWITCH** 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: **WINDSHIELD WIPERS** Single Motor, Electric, Cowl Mounted

: **WIRING, CHASSIS** Color Coded and Continuously Numbered

POWER SOURCE Cigar Type Receptacle without Plug and Cord

ALTERNATOR {Leece-Neville AV1160P2D13} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, with Remote Sense

ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket

BODY BUILDER WIRING INSIDE CAB; Includes Sealed Connectors for Tail/Amber, Turn/Marker/Backup/Accessory, Power/Ground, and Stop/Turn

BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 2775CCA Total

■ **2-WAY RADIO** Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/3MM Auxiliary Input, MP3, Apple Device Play & Control, Bluetooth for Phone & Music, with Multiple Speakers

Vehicle Specifications
2019 7400 SFA 4X2 (SA525)

Description

BACK-UP ALARM Electric, 102 dBA

TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch

AUXILIARY HARNESS 5.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications

HORN, ELECTRIC Disc Style

BATTERY BOX Steel with Plastic Cover, 18" Wide, 2, 3, or 4 Battery Capacity, Mounted Right Side Back of Cab

SWITCH, BODY CIRCUITS, MID for Bodybuilder, 6 Momentary Switches in Instrument Panel; One Power Module with 6 Channels, 20 Amp Max. Per Channel, 80 Amp Max Output, Switches Control Power Module Through Multiplex Wiring, Mounted in Cab Behind Driver Seat

HORN, AIR Black, Single Trumpet, Air Solenoid Operated

WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection

INDICATOR, LOW COOLANT LEVEL with Audible Alarm

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

BATTERY DISCONNECT SWITCH 300 Amp; Cab Mounted, Disconnects Charging Circuits; Locks with Padlock

HOOD, HATCH (01) for Servicing

GRILLE Stationary, Chrome

FRONT END Tilting, Fiberglass, with Three Piece Construction; for WorkStar/HV

PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "GM"

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines

PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted

ENGINE, DIESEL (Cummins L9 330) EPA 2017, 330HP @ 2000 RPM, 1000 lb-ft Torque @ 1400 RPM, 2200 RPM Governed Speed, 330 Peak HP (Max)

FAN DRIVE (Horton Drivemaster) Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

RADIATOR Cross Flow, Series System; 122B SqIn Aluminum Radiator Core with Internal Water to Oil Transmission Cooler and 1167 In Charge Air Cooler

Includes

: DEAERATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

: RADIATOR HOSES Premium, Rubber

Vehicle Specifications
2019 7400 SFA 4X2 (SA525)

Description

AIR CLEANER Single Element, with Integral Snow Valve and In-Cab Control

Includes

: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted

FEDERAL EMISSIONS (Cummins L9) EPA, OBD and GHG Certified for Calendar Year 2018

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

ACCESSORY WIRING, SPECIAL for Road Speed Wire Coiled Under Instrument Panel for Customer Use

ENGINE CONTROL, REMOTE MOUNTED - No Provision Furnished for Remote Mounted Engine Control

FAN OVERRIDE Manual; with Electric Switch on Instrument Panel, (Fan On with Switch On)

EMISSION COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal located on Driver Door

TRANSMISSION, AUTOMATIC (Allison 3500 RDS) 5th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway

TRANSMISSION SHIFT CONTROL (Allison) Push-Button Type; for Allison 3000 & 4000 Series Transmission

SHIFT CONTROL PARAMETERS Allison S-1 Performance Programming In Primary and Allison Fixed Programming in Secondary

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction

PTO LOCATION Right Side of Transmission

AXLE, REAR, SINGLE (Meritor RS-23-160) Single Reduction, 23,000-lb Capacity, Driver Controlled Locking Differential, 200 Wheel Ends . Gear Ratio: 5.38

Includes

: REAR AXLE DRAIN PLUG (1) Magnetic, For Single Rear Axle

Notes

: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.

: When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance

SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 31,000-lb Capacity, Includes 4500-lb Capacity Multileaf Auxiliary

Notes

: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.

FUEL TANK STRAPS Bright Finish Stainless Steel

LOCATION FUELWATER SEPARATOR Mounted Outside Left Rail, 41" Back of Cab

FUELWATER SEPARATOR (Racor 400 Series,) 12 VDC Electric Heater, Includes Pre-Heater, with Primer Pump, Includes Water-in-Fuel Sensor

■ FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 70 US Gal (265L), with Quick Connect Outlet, Mounted Left Side, Under Cab

DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab

CAB Conventional

Includes

: ARM REST (2) Molded Plastic; One Each Door

: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window

: CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel

Vehicle Specifications
2019 7400 SFA 4X2 (SA525)

Description

: DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted
 : GLASS, ALL WINDOWS Tinted
 : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
 : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side
 : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color
 : STEP (4) Two Steps Per Door

GAUGE CLUSTER English with English Electronic Speedometer

Includes

: GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter, Washer Fluid Level
 : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout
 : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)

GAUGE, AIR CLEANER RESTRICTION (Filter-Minder) with Black Bezel Mounted in Instrument Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

GAUGE, DEF FLUID LEVEL

SEAT, DRIVER (National 2000) Air Suspension, High Back with Integral Headrest, Cloth, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust

Includes

: SEAT BELT 3-Point, Lap and Shoulder Belt Type

MIRROR, CONVEX, LOOK DOWN (Lang Mekra) Right Side; 6" x 10 1/4"

GRAB HANDLE Chrome; Towel Bar Type with Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar

SEAT, PASSENGER (National) Non Suspension, High Back, Fixed Back, Integral Headrest, Cloth

MIRRORS (2) (Lang Mekra) Rectangular, Thermostatically Controlled Heated Heads, Black Heads, Brackets and Arms, Breakaway Type, 7.55" x 14.1" Integral Convex Both Sides, 102" Inside Spacing

WINDSHIELD Heated, Single Piece

ARM REST, RIGHT, DRIVER SEAT

AIR CONDITIONER (Blend-Air) with Integral Heater & Defroster

Includes

: HEATER HOSES Premium
 : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps
 : REFRIGERANT Hydrofluorocarbon HFC-134A

INSTRUMENT PANEL Center Section, Flat Panel

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

HVAC FRESH AIR FILTER

STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

CAB INTERIOR TRIM Deluxe

Includes

: CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering
 : CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets and CB Radio Pocket
 : DOOR TRIM PANELS Molded Plastic; Driver and Passenger Doors
 : FLOOR COVERING Rubber, Black

Vehicle Specifications
2019 7400 SFA 4X2 (SA525)

Description

: DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted
 : GLASS, ALL WINDOWS Tinted
 : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
 : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side
 : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color
 : STEP (4) Two Steps Per Door

GAUGE CLUSTER English with English Electronic Speedometer

Includes

: GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter, Washer Fluid Level
 : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout
 : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)

GAUGE, AIR CLEANER RESTRICTION (Filter-Minder) with Black Bezel Mounted in Instrument Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

GAUGE, DEF FLUID LEVEL

SEAT, DRIVER (National 2000) Air Suspension, High Back with Integral Headrest, Cloth, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust

Includes

: SEAT BELT 3-Point, Lap and Shoulder Belt Type

MIRROR, CONVEX, LOOK DOWN (Lang Mekra) Right Side; 6" x 10 1/4"

GRAB HANDLE Chrome; Towel Bar Type with Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar

SEAT, PASSENGER (National) Non Suspension, High Back, Fixed Back, Integral Headrest, Cloth

• MIRRORS (2) (Lang Mekra) Rectangular, Thermostatically Controlled Heated Heads, Black Heads, Brackets and Arms, Breakaway Type, 7.55" x 14.1" Integral Convex Both Sides, 102" Inside Spacing *Power mirrors*

• WINDSHIELD Heated, Single Piece

ARM REST, RIGHT, DRIVER SEAT

AIR CONDITIONER (Blend-Air) with Integral Heater & Defroster

Includes

: HEATER HOSES Premium
 : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps
 : REFRIGERANT Hydrofluorocarbon HFC-134A

INSTRUMENT PANEL Center Section, Flat Panel

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

HVAC FRESH AIR FILTER

STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

CAB INTERIOR TRIM Deluxe

Includes

: CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering
 : CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets and CB Radio Pocket
 : DOOR TRIM PANELS Molded Plastic; Driver and Passenger Doors
 : FLOOR COVERING Rubber, Black

Vehicle Specifications
2019 7400 SFA 4X2 (SA525)

Description

- : HEADLINER Soft Padded Cloth
- : INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section
- : STORAGE POCKET, DOOR (1) Molded Plastic, Full-Length; Driver Door
- : SUN VISOR (2) Padded Vinyl with Driver Side Toll Ticket Strap, Integral to Console

CAB REAR SUSPENSION Air Bag Type

WHEELS, FRONT (Accuride 29300) DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEELS, REAR (Accuride 29169) DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and Steel Hubs

PAINT IDENTITY, REAR WHEELS Omit Paint on Rear Disc Wheels

(4) TIRE, REAR 11R22.5 Load Range H XDN2 (MICHELIN), 497 rev/mile, 75 MPH, Drive

(2) TIRE, FRONT 315/80R22.5 Load Range L X WORKS Z (MICHELIN), 486 rev/mile, 65 MPH, All-Position

Services Section:

WARRANTY Standard for WorkStar 7300/7400 (4x2, 4x4, 6x4, 6x6), Effective with Vehicles Built January 2, 2015 or Later, CTS-2002U